

# Applanation Tonometers AT 020 and AT 030

**Compact and  
practice-proven**



# Applanation Tonometers AT 020 and AT 030

The AT 020 and AT 030 applanation tonometers from Carl Zeiss were designed on the principle introduced by Professor Goldmann. This principle provides precise measurements of intraocular pressure and today represents the gold standard in tonometry.

Adapters allow the maintenance-free tonometers to be mounted to different slit lamps. Naturally, even with a mounted applanation tonometer, you still have the possibility for later slit lamp extensions.



*SL115 Classic with AT 020*



*SL120 with AT 030*

Technical Data		
Applanation Tonometers	AT 020	AT 030
Measuring body	2 prisms for image splitting	
Diameter of applanation field	3.06 mm (0.12 in)	
Measuring range	0 - 78 mN	
Scale reading	0.98 mN	
Reading of graduated drum	X 10 = intraocular pressure in mm Hg (or conversion to kPa with conversion table)	
Dimensions of tonometer	105 x 40 x 25 mm (4.1 x 1.6 x 1.0 in)	200 x 85 x 218 mm (7.9 x 3.3 x 8.6 in)
Total weight	680 g (1.50 lbs)	245 g (0.54 lbs)

**Carl Zeiss Meditec AG**  
Goeschwitzer Str. 51-52  
07745 Jena  
GERMANY

Phone: +49 36 41 22 03 33  
Fax: +49 36 41 22 01 12  
info@meditec.zeiss.com  
www.meditec.zeiss.com

**Carl Zeiss Meditec Inc.**  
5160 Hacienda Drive  
Dublin, CA 94568  
USA

Phone: +1 925 557 41 00  
Fax: +1 925 557 41 01  
info@meditec.zeiss.com  
www.meditec.zeiss.com

**Publication No: 000000-1741-511**  
The contents of the brochure may differ from the current status of approval of the product in your country. Please contact our regional representative for more information.  
Subject to change in design and scope of delivery and as a result of ongoing technical development. Printed on elemental chlorine-free bleached paper. PUBLICIS 1/2009.  
© 2008 by Carl Zeiss Meditec AG. All copyrights reserved.